

R92PA66 Nylon Peel Ply

■ Product description

R92PA66 is an excellent porous Nylon 66 peel ply or release fabric, it has been heat scoured and stabilized at high temperature.

R92PA66 is free of any release agent or pollution and can be used directly on the surface of the part. After curing it peels quite easily without any residue or small pieces left on the part

Red tracer yarn every 30mm helps to distinguish R92PA66 from the cured laminate. This high quality peel ply has been widely used in wind, marine and large parts production markets.

R92PA66 and generally a Nylon peel ply should not be used on phenolic resin. Make a trial or call our technical team for further advice.

In addition to standard widths mentioned below we can customize widths according quantities required.

■ PROPERTIES

| | |
|-------------------------|--------------------|
| Material | Nylon 66 |
| Maximum Use Temperature | 210°C(410°F) |
| Fabric Weight | 92g/m ² |
| Colour | Pink |
| Release Agent | No |

■ AVAILABILITY&PACKAGING

| | |
|---------------|---|
| Standard Size | 1.52m*100m /5.0'*109yard (Other size on request) |
|---------------|---|

■ Notes

Despite R92PA66 shown high ability to peel from a large panel of resin systems curing within its service temperature, it is highly recommended to make some test prior to use it on larger parts.

Storage: In its original packaging in cool and dry place. Avoid direct sunlight.